



**T/S (Thiele/Small)
Parameter**

XTR-200D2N & D4N

XTR-200 D2N

Size: 200mm (8")
Rms: 500 W
Peak: 1000 W
Fms: 44.5 Hz
Res: 124.9 Ohm
Re: 4.0 Ohm
Qms: 4.60
Qes: 0.36
Qts: 0.33
Rms: 9.8 kg/s
Cms: 0.08 mm/N
Mms: 161 gr
Nref: 0.09 %
Bl: 24.4N/A
SPL: 81.7 dB
VAS: 4.0L
Rp: 47.0 Ohm
Lp: 36.2 mH
Cp: 485.7 uF
Le: 2.26 mH

XTR-200 D4N

Size: 200mm (8")
Rms: 500 W
Peak: 1000 W
Fms: 46.2 Hz
Res: 99.7 Ohm
Re: 7.6 Ohm
Qms: 4.53
Qes: 0.46
Qts: 0.42
Rms: 10.1 kg/s
Cms: 0.08 mm/N
Mms: 157.1 gr
Nref: 0.08 %
Bl: 27.5N/A
SPL: 80.9 dB
VAS: 3.8L
Rp: 71.7 Ohm
Lp: 54.7 mH
Cp: 305.8 uF
Le: 3.49 mH



+ 358 9 8700 200

FIN-01300 Sinikellontie 8, Vantaa

flextron@spldynamics.fi